



FED-X Four Glass Door Bench Fridge - XUB7C22G4V

Quick Overview

- Gross Volume: 554L
- Net Volume: 415L
- Max Ambient Temperature: 43°C; 60%RH
- Temperature Range: -2 to 8 ° C
- Cooling System: Fan-forced cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1669mm W x 580mm D x 564mm H

Description

FED-X Four Glass Door Bench Fridge - XUB7C22G4V

This commercial freezer is perfect for running a busy business and is looking for reliability and performance, ideal choice for restaurants, cafes, fast food operations, butcheries, and convenience stores. With fan-forced cooling that ensures even cool air distribution, there will be no warm spots, and your food will be safe. This unit is designed for you to be able to maximize the internal space. You can place it under an existing counter or place it against the wall. Equipped with heavy-duty castors (brake type at the front), you can easily move the unit out for cleaning or maintenance.

Constructed with a stainless steel interior and exterior, your unit is easy to clean and is made strong to withstand the rigors of a busy operation. This unit has 4 see-through self-closing glass doors allowing you to find, choose, and pick what you need as well as do inventory with much ease. All doors are self-closing and fitted with heavy-duty magnetic seals to retain food's optimal quality. You can set your ideal temperature with its user-friendly digital control. This unit is GN-compatible and comes with a single shelf. We can provide Splashback tops as well as a 2 and 3 solid drawer option in lieu of a door, which is available upon request. This underbench fridge's build quality, specifications, and functionality meet food, health, and safety standards.

*Due to its design, this unit can be placed against the wall.

*Tropicalised for Australian conditions.

- Gross Volume: 554L
- Net Volume: 415L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -2 to 8 °C
- Cooling System: Fan-forced cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 1669mm W x 580mm D x 564mm H

MAIN FEATURES

- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- EBM-PAPSTt evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- The unit can be placed against the wall
- LED Lighting Inside

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	4
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	554L
Net Volume	415L
Max Ambient Temperature	43 °C, 60%RH
Temperature Range	-2 to 8 ° C
Total Energy Consumption	5.396 kWh/24h
Net Weight (Kg)	158
Width (mm)	2230
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	2260
Packing Depth (mm)	730
Packing Height (mm)	910
Power	240V; 345W/2.0A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice