



FED-X S/S Single full Door Upright Freezer - XURF400SFV

Quick Overview

- Gross Volume: 429L
- Net Volume: 333L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -18 to -22 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 567mm D x 1394mm H

Description

FED-X S/S Single full Door Upright Freezer - XURF400SFV

Key Features

- Gross Volume: 429L
- Net Volume: 333L
- Max Ambient Temperature: 43 ° C, 60%RH
- Temperature Range: -18 to -22 ° C

- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 567mm D x 1394mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	1
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	429L
Net Volume	333L
Max Ambient Temperature	43 °C, 60%RH
Temperature Range	-18 to -22 °C
Total Energy Consumption	6.57 kWh/24h
Lids	1
Form Factor	Upright
Lid Material	Solid
Net Weight (Kg)	111
Width (mm)	680
Depth (mm)	740
Height (mm)	2000
Packing Width (mm)	710
Packing Depth (mm)	740
Packing Height (mm)	2150
Power	240V, 450W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice