



FED-X S/S Single Full Door Upright Fridge - XURC600SFV

Quick Overview

- Gross Volume: 618L
- Net Volume: 396L
- Max Ambient Temperature: 43°C; 60%RH
- Temperature Range: -2 to +8 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H

Â

Description

FED-X S/S Single Full Door Upright Fridge - XURC600SFV

Key Features

- Gross Volume: 618L
- Net Volume: 396L
- Max Ambient Temperature: 43 °C, 60%RH
- Temperature Range: -2 to +8 °C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 564mm W x 682mm D x 1394mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	1
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	618L
Net Volume	396L
Max Ambient Temperature	43 °C, 60%RH
Temperature Range	-2 to +8 ° C
Total Energy Consumption	2.22 kWh/24h
Net Weight (Kg)	115
Width (mm)	680
Depth (mm)	810+30
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V, 195W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice