



FED-X S/S Three Door Bench Freezer - XUB6F18S3V

Quick Overview

- Gross Volume: 339L
- Net Volume: 254L
- Max Ambient Temperature: 38°C; 60%RH
- Temperature Range: -18 to -22°C
- Cooling System: Fan-forced cooling
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- The unit can be placed against a wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1234mm W x 480mm D x 564mm H

Description

FED-X Stainless Steel Three Door Bench Freezer - XUB6F18S3V

Key Features

- Gross Volume: 339L
- Net Volume: 254L
- Max Ambient Temperature: 38°C, 60%RH

- Temperature Range: -18 to -22 ° C
- Cooling System: Fan-forced cooling
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- 1 shelf per door, additional shelf sets available
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- The unit can be placed against a wall
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1234mm W x 480mm D x 564mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

| | |
|--------------------------|---|
| Product Condition | New |
| Doors | 3 |
| Door Type | Hinged Doors |
| Body | Stainless Steel |
| Gross Volume | 339L |
| Net Volume | 254L |
| Max Ambient Temperature | 38 °C, 60%RH |
| Temperature Range | -18 to -22 °C |
| Total Energy Consumption | 8.515 kWh/24h |
| Lids | 3 |
| Form Factor | Workbench |
| Lid Material | Solid |
| Net Weight (Kg) | 107 |
| Width (mm) | 1795 |
| Depth (mm) | 600 |
| Height (mm) | 850 |
| Packing Width (mm) | 1825 |
| Packing Depth (mm) | 630 |
| Packing Height (mm) | 910 |
| Power | 240V; 50V; 10A; 520W |
| Warranty | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |