



FED-X S/S Two Door Bench Fridge - XUB7C13S2V

Quick Overview

- Gross Volume: 282L
- Net Volume: 186L
- Max Ambient Temperature: 43°C; 60%RH
- Temperature Range: -2 to 8°C
- Cooling System: Fan-forced, dry cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditioner-friendly Digital controls
- Rapid recovery rate
- Optional 2 3-drawer units are available instead of doors
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front-wheel brake units can be placed against the wall.
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 799mm W x 580mm D x 564mm H

Â

Description

FED-X Stainless Steel Two Door Bench Fridge - XUB7C13S2V

Key Features

- Gross Volume: 282L
- Net Volume: 186L
- Max Ambient Temperature: 43 °C , 60%RH
- Temperature Range: -2 to 8 ° C
- Cooling System: Fan-forced, dry cooling
- Compressor: Embraco/Secop
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- 1 shelf per door, GN1/1 pan compatible
- Self-closing doors with heavy-duty magnetic door seals
- 60mm HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditioner-friendly Digital controls
- Rapid recovery rate
- Optional 2 3-drawer units are available instead of doors
- EBM-PAPST evaporator and condenser fans
- Heavy-duty castors with front-wheel brake units can be placed against the wall.
- Weight loading per shelf: 40kg
- Refrigerant: R290
- Dimensions (Internal): 799mm W x 580mm D x 564mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	282L
Net Volume	186L
Max Ambient Temperature	43 °C, 60%RH
Temperature Range	-2 to 8 °C
Total Energy Consumption	2.623 kWh/24h
Net Weight (Kg)	102
Width (mm)	1360
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	730
Packing Depth (mm)	1390
Packing Height (mm)	910
Power	240V; 215W/1.3A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice