



## FED-X S/S Two Full Door Upright Freezer - XURF1200SFV

### Quick Overview

- Gross Volume: 1236L
- Net Volume: 791L
- Max Ambient Temperature: 43°C, 60%RH
- Temperature Range: -18 to -22 ° C
- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H

### Description

FED-X S/S Two Full Door Upright Freezer - XURF1200SFV

### Key Features

- Gross Volume: 1236L
- Net Volume: 791L
- Max Ambient Temperature: 43 ° C, 60%RH
- Temperature Range: -18 to -22 ° C

- Cooling System: Fan-forced cooling
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy-duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital Controls
- Integrated door handle for easy cleaning
- Heavy-duty evaporator and condenser fans
- Heavy-duty castors with front-wheel brakes
- Weight loading per shelf: 40kg
- Dimensions (Internal): 1224mm W x 682mm D x 1394mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

## Your Shipping Specifications

---

|                          |   |
|--------------------------|---|
| Product Condition        | New   |
| Doors                    | 2   |
| Door Type                | Hinged Doors  |
| Body                     | Stainless Steel   |
| Gross Volume             | 1236L   |
| Net Volume               | 791L  |
| Max Ambient Temperature  | 43 °C, 60%RH  |
| Temperature Range        | -18 to -22 ° C  |
| Total Energy Consumption | 12.33 kWh/24h   |
| Lids                     | 2   |
| Form Factor              | Upright   |
| Lid Material             | Solid   |
| Net Weight (Kg)          | 177   |
| Width (mm)               | 1340  |
| Depth (mm)               | 840   |
| Height (mm)              | 2000  |
| Packing Width (mm)       | 1365  |
| Packing Depth (mm)       | 855   |
| Packing Height (mm)      | 2070  |
| Power                    | 240V, 700W/4.6A   |
| Warranty                 | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |