



FED-X Six Drawer Salad Prep Fridge - XSS7C18S3V-6D

Quick Overview



- Gross Volume: 417L
- Net Volume: 400L
- Max Ambient Temperature: 43°C, 60%RH
- Cooling System: Fan forced cooling
- Temperature Range: +2 to +8 ° C
- Compressor: Cubigel
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Compatible for 8 x 1/3 GN Pan up to 150mm deep
- 60mm HFCs and CFCs-free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty 6 drawer
- Ebm-papst evaporator and condenser fans
- Heavy-duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- The display top can hold temperature for up to 4 hours from a pre-chilled environment

Description

FED-X S/S Three Door Sandwich Counter - XSS7C18S3V

Key Features

- Gross Volume: 417L
- Net Volume: 400L
- Max Ambient Temperature: 43 °C, 60%RH
- Cooling System: Fan forced cooling
- Temperature Range: +2 to +8 ° C

- Compressor: Cubigel
- Controller: Dixell
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Compatible for 8 x 1/3 GN Pan up to 150mm deep
- 60mm HFCs and CFCs-free foam body insulation
- Tropicalised for Australian conditions
- User-friendly Digital controls
- Rapid recovery rate
- Heavy-duty 6 drawer
- Ebm-papst evaporator and condenser fans
- Heavy-duty castors with front wheel brakes
- Weight loading per shelf: 40kg
- Refrigerant: R290
- The display top can hold temperature for up to 4 hours from a pre-chilled environment

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	6
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	417L
Net Volume	400L
Max Ambient Temperature	43 , 60%RH
Temperature Range	+2 to +8 ° C
Net Weight (Kg)	130
Width (mm)	1795
Depth (mm)	700
Height (mm)	1406
Packing Width (mm)	1830
Packing Depth (mm)	730
Packing Height (mm)	1160
Power	240V; 50V; 10A; 320W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice