



FED-X Two Door Salad Prep Fridge with Curve Glass Top - XTHP2100SALGC

Quick Overview

- Gross Volume: 282L
- Net Volume: 186L
- Max Ambient Temperature: 43°C, 60%RH
- Cooling System: Fan-forced cooling
- Temperature range: +2 to +8 ° C
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Open top suitable for multiple pan configurations (Pans and lids are not included)
- Replaceable magnetic door seals
- User-friendly Digital controls
- Integrated cutting board made from high-density polyethylene
- Heavy-duty castors with front-wheel brakes
- Pan and pan cover must be used to ensure the correct operating temperature
- Weight loading per shelf: 40kg
- Dimensions (internal): 799mm W x 580mm D x 564mm H

Description

FED-X Two Door Salad Prep Fridge with Curve Glass Top - XTHP2100SALGC

Key Features

- Gross Volume: 282L
- Net Volume: 186L

- Max Ambient Temperature: 43 °C, 60%RH
- Cooling System: Fan-forced cooling
- Temperature range: +2 to +8 °C
- Compressor: Cubigel
- Controller: Dixell
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Open top suitable for multiple pan configurations (Pans and lids are not included)
- Replaceable magnetic door seals
- User-friendly Digital controls
- Integrated cutting board made from high-density polyethylene
- Heavy-duty castors with front-wheel brakes
- Pan and pan cover must be used to ensure the correct operating temperature
- Weight loading per shelf: 40kg
- Dimensions (internal): 799mm W x 580mm D x 564mm H

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration within 14 Days of Invoice

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	282L
Net Volume	186L
Max Ambient Temperature	43 , 60%RH
Temperature Range	+2 to +8 ° C
Net Weight (Kg)	105
Width (mm)	1360
Depth (mm)	700
Height (mm)	1320
Packing Width (mm)	1390
Packing Depth (mm)	730
Packing Height (mm)	910
Power	240V; 50V; 10A; 215W
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice