



GN2100TNG - 2 Glass Door Gastronorm Bench Fridge

Quick Overview

- Gross Volume: 314L
- Net Volume: 205L
- Max Ambient Temperature: 30°C, 55%RH
- Temperature Range: -2 to 8 ° C
- One Level Of Shelving Plus Floor
- German B&Bm-Pabst Fans
- Italian (Carel) Digital Temp. Controls & Read-Out
- Units Can Be Easily Slid Open For Cleaning & Maintenance
- Internal Corners Rounded For Hygiene & Easy Cleaning
- Fan-Forced Evaporator Cooling
- Auto Defrost
- Self-Evaporating Drainage
- Insulation Is CFC & HCFC Free
- Extremely Efficient Self-Closing Doors
- Heated Door Frame
- 100mm Wall Clearance Required for Ventilation
- Castors
- LED Lighting Inside
- The unit can be placed against the wall
- Stainless Steel Interior & Exterior
- Gastronorm
- Matches Gn Series Bench Freezers
- Gal Metal Back

Description

GN2100TNG - 2 Glass Door Gastronorm Bench Fridge

Key Features

- Gross Volume: 314L
- Net Volume: 205L

- Max Ambient Temperature: 30°C, 55%RH
- Temperature Range: -2 to 8 ° C
- One Level Of Shelving Plus Floor
- German EBM-Pabst Fans
- Italian (Carel) Digital Temp. Controls & Read-Out
- Units Can Be Easily Slid Open For Cleaning & Maintenance
- Internal Corners Rounded For Hygiene & Easy Cleaning
- Fan-Forced Evaporator Cooling
- Auto Defrost
- Self-Evaporating Drainage
- Insulation Is CFC & HCFC Free
- Extremely Efficient Self-Closing Doors
- Heated Door Frame
- 100mm Wall Clearance Required for Ventilation
- Castors
- LED Lighting Inside
- The unit can be placed against the wall
- Stainless Steel Interior & Exterior
- Gastronorm
- Matches Gn Series Bench Freezers
- Gal Metal Back

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Product Condition	New
Doors	3
Door Type	Hinged Doors
Body	Stainless Steel
Gross Volume	314L
Net Volume	205L
Max Ambient Temperature	30°C, 55%RH
Temperature Range	-2 to 8 ° C
Total Energy Consumption	2.3 kWh/24h
Net Weight (Kg)	98
Width (mm)	1360
Depth (mm)	700
Height (mm)	850
Packing Width (mm)	740
Packing Depth (mm)	1380
Packing Height (mm)	920
Power	240V; 300W/10A
Warranty	2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice