



Bonvue Chilled Counter-Top Food Display - HTR120N

Quick Overview

- Gross Volume: 115L
- Net Volume: 78L
- Max Ambient Temperature: 32°C
- Temperature Range: 3 to 8 ° C
- Sliding Rear Doors
- CFC-free refrigerant and foam
- A ventilated refrigeration compartment gives better air circulation
- Auto defrosting
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Curved glass food display
- Fan-forced air flow
- LED lamp
- HC refrigerant
- 2 adjustable Shelving
- Refrigeration Unit Is Fully Self-Contained In The Base (No Well Cut-Out Is Required)
- Internal dimension: 663 x 498 x 384 mm
- Shelf dimension: One 642 x 372 + One 642 x 408 mm
- Front glass: Tempered double-glazed glass

Description

Bonvue Chilled Counter-Top Food Display - HTR120N

The standard chilled display from the renowned commercial refrigeration brand, Bonvue, contains decent power.

One of Bonvue ' s standardised benchtop displays, this piece works wonders in keeping your meals and ingredients chilled and made ready for serving.

Encased with a picturesque curved glass display, this unit is built with a strong stainless-steel base, digital temp controller, LED

display, and a perfected ventilated refrigeration system.

Three Levels Of Display In A Stainless Steel And Glass Cabinet

Key Features

- Gross Volume: 115L
- Net Volume: 78L
- Max Ambient Temperature: 32
- Temperature Range: +3 to +8 ° C
- Sliding Rear Doors
- CFC-free refrigerant and foam
- A ventilated refrigeration compartment gives better air circulation
- Auto defrosting
- Electronic thermostat and digital LED temperature display for accurate control and easy reading
- Curved glass food display
- FFan-forcedairflow
- LED lamp
- HC refrigerant
- 2 adjustable Shelving
- Refrigeration Unit Is Fully Self-Contained In The Base (No Well Cut-Out Is Required)
- Internal dimension: 663 x 498 x 384 mm
- Shelf dimension: One 642 x 372 + One 642 x 408 mm
- Front glass: Tempered double-glazed glass

1 Year Parts and Labour Warranty

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Sliding Doors
Body	Stainless Steel
Gross Volume	115L
Net Volume	78L
Max Ambient Temperature	32
Temperature Range	+3 to +8 ° C
Total Energy Consumption	4.054 (kWh/24h)
Net Weight (Kg)	64
Width (mm)	695
Depth (mm)	498
Height (mm)	384
Packing Width (mm)	753
Packing Depth (mm)	624
Packing Height (mm)	710
Power	240V; 160W / 10A
Warranty	1 Year Parts and Labour